

(1390,REV. 5-93) US DEPT. OF COMMERCE PATENT &amp; TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER  
110116

**TRANSMITTAL LETTER TO THE  
UNITED STATES  
DESIGNATED/ELECTED OFFICE  
(DO/EO/US) CONCERNING A FILING  
UNDER 35 U.S.C. 371**

U.S. APPLICATION NO.  
(if known, sec 37 C.F.R.1.5)**09/889305**INTERNATIONAL APPLICATION NO.  
PCT/GB00/04403INTERNATIONAL FILING DATE  
November 17, 1999PRIORITY DATE CLAIMED  
November 22, 1999TITLE OF INVENTION  
OPTICAL MEASURING APPARATUS FOR MEASURING OBJECTS ON MACHINESAPPLICANT(S) FOR DO/EO/US  
Victor G. STIMPSON, Jon P. FUGE, William K. DAVIES, Norman J. LEETE and Colin T. BELL

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☒ has been transmitted by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
  - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ have been transmitted by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

**Items 11. to 16. below concern other document(s) or information included:**


11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.
- ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ Entitlement to small entity status is hereby asserted.
16. ☐ Other items or information:

U.S. APPLICATION NO. (if known, see 37 C.F.R. 1.5) <b>097/889305</b>	INTERNATIONAL APPLICATION NO. PCT/GB00/04403	ATTORNEY'S DOCKET NUMBER 110116
--	--	---------------------------------

17. <input checked="" type="checkbox"/> The following fees are submitted:  <b>Basic National fee (37 CFR 1.492(a)(1)-(5)):</b>  Search Report has been prepared by the EPO or JPO .... \$860.00  International preliminary examination fee paid to USPTO (37 CFR 1.482) ..... \$690.00  No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) ..... \$710.00  Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... \$1,000.00  International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) ..... \$ 100.00  <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b> \$860.00	CALCULATIONS      PTO USE ONLY																																												
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).	\$																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Claims</th> <th style="width: 25%;">Number Filed</th> <th style="width: 25%;">Number Extra</th> <th style="width: 25%;">Rate</th> </tr> </thead> <tbody> <tr> <td>Total Claims</td> <td>9- 20 =</td> <td></td> <td>X \$ 18.00</td> </tr> <tr> <td>Independent Claims</td> <td>2- 3 =</td> <td></td> <td>X \$ 80.00</td> </tr> <tr> <td colspan="2">Multiple dependent claim(s) (if applicable)</td> <td></td> <td>+ \$270.00</td> </tr> <tr> <td colspan="3"><b>TOTAL OF ABOVE CALCULATIONS =</b></td> <td>\$</td> </tr> <tr> <td colspan="3">Reduction by 1/2 for filing by small entity, if applicable.</td> <td>- \$</td> </tr> <tr> <td colspan="3"><b>SUBTOTAL =</b></td> <td>\$860.00</td> </tr> <tr> <td colspan="3">Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).</td> <td>\$</td> </tr> <tr> <td colspan="3"><b>TOTAL NATIONAL FEE =</b></td> <td>\$860.00</td> </tr> <tr> <td colspan="3"></td> <td>Amount to be refunded \$</td> </tr> <tr> <td colspan="3"></td> <td>Charged \$</td> </tr> </tbody> </table>	Claims	Number Filed	Number Extra	Rate	Total Claims	9- 20 =		X \$ 18.00	Independent Claims	2- 3 =		X \$ 80.00	Multiple dependent claim(s) (if applicable)			+ \$270.00	<b>TOTAL OF ABOVE CALCULATIONS =</b>			\$	Reduction by 1/2 for filing by small entity, if applicable.			- \$	<b>SUBTOTAL =</b>			\$860.00	Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).			\$	<b>TOTAL NATIONAL FEE =</b>			\$860.00				Amount to be refunded \$				Charged \$	
Claims	Number Filed	Number Extra	Rate																																										
Total Claims	9- 20 =		X \$ 18.00																																										
Independent Claims	2- 3 =		X \$ 80.00																																										
Multiple dependent claim(s) (if applicable)			+ \$270.00																																										
<b>TOTAL OF ABOVE CALCULATIONS =</b>			\$																																										
Reduction by 1/2 for filing by small entity, if applicable.			- \$																																										
<b>SUBTOTAL =</b>			\$860.00																																										
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).			\$																																										
<b>TOTAL NATIONAL FEE =</b>			\$860.00																																										
			Amount to be refunded \$																																										
			Charged \$																																										

a. <input checked="" type="checkbox"/> Check No. <u>120950</u> in the amount of <u>\$860.00</u> to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$_____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Director is hereby authorized to charge any additional fees which may be required, or credit any overpayment, to Deposit Account No. <u>15-0461</u> . A duplicate copy of this sheet is enclosed.	 NAME: James A. Oliff REGISTRATION NUMBER: 27,075  NAME: Thomas J. Pardini REGISTRATION NUMBER: 30,411
--	--

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:  
 OLIFF & BERRIDGE, PLC  
 P.O. Box 19928  
 Alexandria, Virginia 22320

Date: July 16, 2001

# OPTICAL MEASURING APPARATUS FOR MEASURING OBJECTS ON MACHINES

The present invention relates to an optical measuring apparatus which enables a coordinate positioning machine (such as a machine tool) to determine the position of an object relative to a reference point. It may, for example, be employed on a machine tool for toolsetting operations.

A known tool setting device for use on a machine tool includes a light source which generates a fine beam of light which is incident upon a detector. During a toolsetting operation, the machine is operated to move the tool in a direction transverse to the direction of propagation of the light beam until a part of the tool interrupts passage of the light beam. Detection of this interruption is used to produce a trigger signal in the detecting unit, which is used by the machine to establish the relative position of its moving parts in order to determine dimensions of the tool. Such devices are known, for example, from German Patent Nos. DE 42 385 04 and DE 42 448 69, French Patent No. 2,343,555, European Patent No. 98,930 and US Patent No. 4,518,257. The devices may be used additionally for measuring the length or diameter of a tool to monitor tool breakage or wear.

The devices disclosed in the above-mentioned patent specifications use a narrow light beam into or through which the tool is passed. The detection units detect when the tool breaks into the beam from the resulting drop in the intensity of the light falling on them. The trigger signal may be produced as a result of a predetermined drop in the intensity of light falling on the detector as the tool enters the beam.

A problem which arises with such optical measuring apparatus is that coolant used on the machine can drip through the beam, or be thrown off the rotating tool into the beam, during the measuring operation and give rise to false trigger signals.

One method of overcoming this problem which is currently used, is to program the software in the machine controller to perform several measurements until a pre-selected number of measurements falling within a given tolerance have been obtained. The position of the tool is then assumed to be the average of these measurements. This method can give rise to an unacceptable increase in the measurement cycle time if a significant number of repeat measurements have to be taken.

The present invention seeks to alleviate this problem by providing a method of measurement which can differentiate between a genuine tool detection signal, and a signal produced by a coolant drip.

According to one aspect of the present invention there is provided a method of making measurements of an object on a machine tool using an optical measuring apparatus which includes a light source which generates a beam of light which is incident upon a detector, the method comprising the steps of:

- generating a detection signal within the detector each time the beam is interrupted;
- evaluating the frequency and/or duration of the occurrences of said detection signals;
- emitting an output signal from the detector only if a further detection signal is also present within the detector in a specified time interval from the

generation of an earlier detection signal.

The timing of the detection signals can be achieved in various ways.

5

In one embodiment of the invention the tool is rotated, preferably, at a known specific speed. This gives rise to the generation of a regular sequence of said signals within the detector as the cutting edge (or edges) of the tool interrupt the beam. The generation of the first one of the said signals is used to initiate a timing sequence within the detector which sets a time interval ( $t_1$ ) substantially equal to the time taken for one revolution of the tool, followed by a second time interval ( $t_2$ ) which is substantially shorter than ( $t_1$ ). If it is the tool which has generated the signals in the detector then a second signal will be generated in the time interval ( $t_2$ ) as the cutting edge of the tool comes round again, and if this happens, the detector emits the output signal.

Alternatively, the generation of a detection signal within the detector can be used to start a clock which emits pulses of short duration synchronised with the speed of rotation of the tool. Again, if a second detection signal is generated within the detector during such a pulse then the detector emits an output signal. A number of clocks may be used which start sequentially as the detector generates its detection signals, and each of which stops if no second detection signal is generated within the detector during the next one of its pulses.

The invention also includes optical measuring apparatus for carrying out the method which comprises a light source for generating a light beam and a detector for

receiving said beam and which generates a signal when the beam is interrupted, wherein the detector includes a detection circuit which generates a detection signal each time the beam is interrupted, and signal

5 processing means for evaluating the frequency and/or duration of the occurrences of said detection signals and which emits an output signal only if a second signal is generated by the detection circuit within a specified time interval after the occurrence of an  
10 earlier detection signal.

Examples of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

15 Fig 1 is a perspective view of an optical measuring apparatus incorporating the present invention;

Fig 2 is a representation of the output of the detector of Fig 1; and

20 Fig 3 is a block diagram representing the basic elements of the apparatus;

Fig 4 illustrates in lines 4a to 4f the signals generated in various parts of the signal processing circuit of the detector.

25 Referring now to Fig 1, the optical measuring apparatus is shown in a set up arranged to operate as a toolsetting apparatus, suitable for use, for example, on a machine tool. The apparatus includes a light  
30 emitting unit 10 which emits a beam 12 of light, and a light detecting unit 14, where the light beam 12 is detected. Power and signal control cables to the light emitting and detecting units 10,14 are routed via inlet ports 16, and both the units 10,14 are advantageously  
35 mounted, via pillars 18, on the base of the machine, either via an intermediate base 20, to which they are

both mounted, or directly to the base of the machine upon which they are to be employed.

In operation, the apparatus is used for toolsetting by operating the machine on which the apparatus is mounted to move the tool in a direction transverse to the direction in which the beam 12 is propagating. When a predetermined level of occlusion of the beam has been established, the detecting unit 14 emits a trigger signal which is used by the machine to determine the relative position of its relatively movable parts, thereby to enable dimensions of the tool to be determined.

Further mechanical and optical details of an example of such an apparatus are described in our European Patent Application No. 00303749.6 (which is hereby incorporated into this specification by reference) and are not therefore reproduced here.

Fig 2 shows the output of the detector in various circumstances. The detector output goes high (i.e. produces a detection signal) as shown by a voltage pulse when the beam is occluded to said predetermined extent. As can be seen by the first pulse S1 at the left-hand side of the drawing this can occur when a coolant drip passes through the beam.

In the first instance however, the coolant drip is a single occurrence, which produces a single short duration pulse.

When the edge of the rotating cutting tool breaks the beam there is also a short duration pulse S2, but this is followed by further pulses S3 (only one shown) as the same cutting edge comes into the beam again, or as other cutting edges of a multi-edged tool cut the beam

in turn.

In order to be able to identify the difference between occlusion of the beam by a drip, and occlusion of the beam by the edge of the cutting tool for the first time (which is the event which is required to be detected to measure the position of the cutting edge), the invention provides that a timer in the detector sets a first time interval  $t_1$  simultaneously with the detector generating its detection signal. In a specific embodiment the time interval  $t_1$  is arranged to be equal to the length of time it takes for one revolution of the tool. At the end of the time interval  $t_1$  the timer sets a shorter time interval  $t_2$ .

The detector monitors the time interval  $t_2$  for a second detection signal which is unlikely to occur if the first signal is a drip. This can be detected by either a high state of the output signal or a rising edge. If the second detection signal is present the detector issues a "skip" or trigger signal at the end of time interval  $t_2$ .

Since the time intervals  $t_1$  and  $t_2$  are accurately known the instant of the occurrence of the first rising edge of the detector output due to a cutting edge of the tool obscuring the beam can be calculated.

In order to calculate the timings, the speed of rotation of the machine spindle, and hence the cutting tool must be set. In order to keep the time for the measuring operation down a reasonable level, the spindle speed was set during experimentation at 1000rpm so that  $t_1$  was ostensibly 60ms. The interval  $t_2$  however, has to be large enough to cater for slight variations in spindle speed for example up to 5%, which



would cause a 3ms variation in  $t_1$ .

To centre the trigger signal in the time interval  $t_2$ ,  $t_2$  is set at  $t_1 + \frac{1}{2}t$  which must be equal to 60ms. Thus  $t_1$  was actually set at 58.5ms.

It is not necessary for the speed of rotation of the tool to be known prior to measurements being taken since it can be measured by timing the distance between the rising edges of the first two consecutive pulses out of the sequence of pulses generated by the detector. The time interval ( $t_1$ ) can then be set between the second and third rising edges and ( $t_2$ ) can be timed from the third rising edge.

The basic elements of the apparatus of the invention are shown in block diagram form in Fig 3. The light beam 12 from the transmitter 10 entering the detector 14 impinges on a photodetector in a detection circuit 72 which produces the signals when the beam is interrupted. Signals generated in the detection circuit 72 are passed to a signal processor 74 which includes the necessary timing devices for signal analysis. The detector output signals are passed directly to the machine controller 80 which stops the machine, and evaluates the machine scale readings to determine the position of the machine.

Fig 4 illustrates an alternative embodiment in which one or more clocks in the detector are used, each of which generates a series of pulses initiated by the detector issuing a signal to indicate that the beam has been interrupted;

Fig 4a shows an example of a series of events created by a mixture of teeth and drips interrupting the beam;

Fig 4b shows the signals created by these events converted to pulses at the output of a comparator in the signal processor of the detector;

Fig 4c shows the situation which occurs in the detector when a single clock is used;

Fig 4d shows the situation which occurs in the detector when a second clock is used;

Figs 4e and 4f respectively show the results of combining the comparator output with the outputs of clock 1 and clock 2.

It can be seen from Fig 4a that the drips occur and interrupt the beam at random intervals while the beam interruptions caused by the edge of the tool occur at regular intervals. Each beam interruption is labelled as a numbered event E.

Fig 4b shows the comparator output pulses corresponding to the events.

Fig 4c shows that the first clock starts when event E1 occurs but because there is no event occurring when the second clock pulse is sent to the signal processor the clock is stopped. The clock is started again on the occurrence of event E3 which is also a drip, but again because its second pulse occurs between events E4 and E5 it will not see event E4 and will stop. The situation is the same when it starts again at event E5. Only when it starts again at event E7 will its pulses be synchronised with the occurrences of the cutting edge of the tool interrupting the beam at event E9 and beyond so that a trigger signal will be produced on event E7. This signal will have missed the first occurrence of the cutting edge interrupting the beam at E6 and will produce an erroneous reading.

With the embodiment which uses two clocks however, as shown in Fig 4d, the second clock will be started on event E6 because at that time the first clock is running. Since event E6 is an interruption of the beam  
5 by an edge of the cutting tool there will be a further event E7 occurring when the clock pulse is generated. The signal processor will recognise that the clock pulses and the events have now become synchronised and will generate a trigger signal on the rising edge of  
10 the pulse. Since the generation of the clock pulses and the beam interruptions are synchronised, the time at which the first beam interruption occurred can easily be determined.

15 The situation is less complex if the first event is caused by a cutting edge of the tool, because the first clock will start and will see a synchronised event during its first pulse and cause a trigger signal at that time.

20 If a drip occurs between the first and second events this will be ignored by the first clock since it will not occur during its first pulse. Hence the drip will not affect the generation of the trigger signal under  
25 these circumstances.

Although the invention has been described using one or two clocks, other benefits may be achieved if more clocks were used which are set at different  
30 frequencies.

For example, the apparatus could be used at different speeds of spindle rotation without having to re-set the timing of the existing clocks, and additional clocks  
35 would allow the apparatus to deal with an atmosphere where a lot of drips could be expected. The number of

clocks used would be a trade-off between the benefits to be obtained, and the expense of the additional signal processing capability required.

5 The invention can also be used when the tool is not rotating to measure tool length or diameter during tool setting, or for tool breakage detection. In such an embodiment the tool is moved at right angles to the beam until its tip or flank interrupts the beam. The  
10 signal produced by the detector is used to start a clock in the signal processor which evaluates the detector output after a time  $t$ . If the detector output is still high at that time, denoting a signal is still present, the signal processor produces a trigger  
15 signal.

In yet another embodiment, the signal processor may incorporate a device which identifies synchronous events. The inputs to the device are samples at  
20 regular intervals and the samples are stored in a buffer of fixed length, the new contents constantly overriding the old. The buffer can be implemented using a shift register which monitors the detector output and writes its current state into the shift  
25 register each time a sample is taken. If the buffer is split across two bytes, testing for repetitive patterns can be achieved by comparing the two halves. For example, if the sample rate is eight times the speed of rotation of the tool and the result of each sample is  
30 shifted through two eight bit registers, when a first signal occurs this shows up as a high (1) in the first cell of the register. The sample moves through the register until it is passed into the first cell on the second half. If there has been no synchronous event  
35 the sample passes through the register to the end.

11

If however, another high sample is received in the first cell of the first half of the register just as the first sample moves into the first cell of the second half of the register then the two halves will become identical once again and a trigger signal will be issued.

10 The invention has been described with reference to the elimination of spurious trigger signals in an optical measuring apparatus on a machine tool, but may have wider application using other forms of optical measuring apparatus on other types of machine. The scope of the invention is therefore, to be taken as that defined by the appended claims.

## CLAIMS

1. A method of making measurements of an object on a machine using an optical measuring apparatus which includes a light source which generates a beam of light which is incident upon a detector, the method comprising the steps of:

generating a detection signal within the detector each time the beam is interrupted;

evaluating the frequency and/or duration of the occurrences of said detection signals;

emitting an output signal from the detector only if a further detection signal is present within the detector in a specified time interval from the generation of an earlier detection signal.

2. A method according to claim 1 and comprising the further steps of:

rotating the object;

generating a first time interval ( $t_1$ ) which is dependent on the speed of rotation of the object; and generating the specified time interval as a time interval ( $t_2$ ) which is shorter than ( $t_1$ ) and commences at the end of the interval ( $t_1$ ).

3. A method according to claim 2 wherein the object is a tool on a machine tool and the tool is rotated at a known specific speed and the time interval ( $t_1$ ) is substantially equal to the time taken for one revolution of the tool.

4. A method according to claim 3 wherein the apparatus further includes a clock, the method comprising the further steps of:

rotating the tool;

causing the clock to initiate the emission of a

series of pulses of short duration which are synchronised with the speed of rotation of the tool, the first pulse being emitted to coincide with a detection signal being generated in the detector;

5 emitting an output signal from the detector only if a detection signal is also present within the detector during the existence of a clock pulse;

stopping the clock if no such detection signal is present in the detector.

10 5. A method according to claim 4 wherein a clock pulse is produced for each revolution of the tool, and an output signal is emitted from the detector only if a detection signal is present with the detector during  
15 the next pulse emitted by the clock following said first pulse.

6. A method according to claim 4 wherein the apparatus includes two clocks the method comprising the  
20 further steps of:

causing a first clock to initiate the emission of a first series of said pulses when a detection signal is generated within the detector;

causing the second clock to initiate the emission  
25 of a second series of said pulses commencing with the generation of a further detection signal within the detector in the interval between two successive pulses of the first clock; and

emitting an output signal from the detector if a  
30 detection signal is also present within the detector during the existence of the next pulse in the second series if the detector has not emitted an output signal based on the first series of pulses.

35 7. A method according to claim 6 wherein the apparatus includes additional clocks, the method

comprising the steps of sequentially initiating the emission of respective series of said pulses if a detection signal is generated within the detector and all of the previously started clocks are running.

5

8. A method according to claim 6 wherein the apparatus includes additional clocks, the method comprising the steps of setting the clocks to produce respective series' of pulses at different frequencies set to coincide with different speeds of rotation of the tool, and causing the initiation of the emission of a said series of pulses appropriate to the speed of rotation of the tool.

10

9. Optical apparatus for measuring objects on machines comprising a light source for generating a light beam and a detector for receiving said beam and which generates a signal when the beam is interrupted, wherein the detector includes a detection circuit which generates a signal each time the beam is interrupted, and signal processing means for evaluating the frequency and/or duration of the occurrences of said signals and which emits an output signal only if a second signal is generated by the detection circuit within a specified time interval after the occurrence of said signal.

20

25

10. Optical measuring apparatus according to claim 9 and wherein the object is a tool on a machine tool.


30

35



1/3

Fig. 1.



2/3

Fig.2.




Fig.3.






Fig.4.



3/3



# Declaration and Power of Attorney Under Patent Cooperation Treaty 35 USC §371(c)(4)

As a below named inventor, I hereby declare that:

my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the invention entitled: Optical Measuring Apparatus For Measuring Objects on Machines

described and claimed in international application number PCT/GB00/04403 filed 17 November 2000 and as amended on \_\_\_\_\_ (if any), the specification and claims of which I have reviewed and understand and for which I solicit a patent.

I acknowledge my duty to disclose information of which I am aware which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a), and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to my international application by me or my legal representatives or assigns, except as follows:

United Kingdom Patent Application No. 9927471.4 filed 22 November 1999  
United Kingdom Patent Application No. 0020929.6 filed 25 August 2000


The priority of the above applications (if any), filed within a year prior to my international application is hereby claimed under 35 USC 119. I hereby appoint the following as my attorneys of record with full power of substitution and revocation to prosecute this application and to transact all business in the Patent Office:

James A. Oliff, Reg. No. 27,075; William P. Berridge, Reg. No. 30,024; Kirk M. Hudson, Reg. No. 27,562;  
Thomas J. Pardini, Reg. No. 30,411 and Edward P. Walker, Reg. No. 31,450

**ALL CORRESPONDENCE IN CONNECTION WITH THIS APPLICATION SHOULD BE SENT TO OLIFF & BERRIDGE, P.O. BOX 19928, ALEXANDRIA, VIRGINIA 22320, TELEPHONE (703) 836-6400.**

I hereby declare that I have reviewed and understand the contents of this Declaration, and that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

3 Full name of Sole or First Inventor Victor G Stimpson  
Given Name Middle Initial Family Name

\*4 Inventor's Signature 

\*5 Date of Signature JULY 5th 2001  
Month Day Year

6 Residence Avening Gloucestershire United Kingdom  
City State or Province Country

7 Citizenship United Kingdom GBX

8 Post Office Address Field House, Tetbury Hill, Avening,  
(Insert complete mailing address, including country) Gloucestershire, GL8 8LT, United Kingdom

\*Note to Inventor: Please sign name on line 4 exactly as it appears in line 3 and insert the actual date of signing on line 5.

IF THERE IS MORE THAN ONE INVENTOR USE PAGE 2 AND PLACE AN "X" HERE ☒

PCT DECLARATION FORM

PAGE 2 OF U.S.A. DECLARATION FORM  
(Discard this page in a sole inventor application)

200 3 Typewritten Full Name of Second Joint Inventor (if any) Jon P Fuge  
Given Name Middle Initial Family Name

\*4 Inventor's Signature [Signature]

\*5 Date of Signature 7 5 2001  
Month Day Year

\*6 Residence Bristol South Gloucestershire United Kingdom  
City State of Province Country

\*7 Citizenship United Kingdom GBX

8 Post Office Address  
(Insert complete mailing address, including country)  
106 Guest Avenue, Emersons Green, Bristol  
South Gloucestershire, BS16 7EA, United Kingdom

300 3 Typewritten Full Name of Third Joint Inventor (if any) William K Davies  
Given Name Middle Initial Family Name

\*4 Inventor's Signature [Signature]

\*5 Date of Signature 7 9 2001  
Month Day Year

\*6 Residence Bristol South Gloucestershire United Kingdom  
City State of Province Country

\*7 Citizenship United Kingdom GBX

8 Post Office Address  
(Insert complete mailing address, including country)  
10 Squires Leaze, Thornbury, Bristol,  
South Gloucestershire, BS35 1TB, United Kingdom

400 3 Typewritten Full Name of Fourth Joint Inventor (if any) Norman J Leete  
Given Name Middle Initial Family Name

\*4 Inventor's Signature [Signature]

\*5 Date of Signature 7 9 2001  
Month Day Year

\*6 Residence Uley Gloucestershire United Kingdom  
City State of Province Country

\*7 Citizenship United Kingdom GBX

8 Post Office Address  
(Insert complete mailing address, including country)  
4 Court Garden, Uley, Gloucestershire,  
GL11 5AH, United Kingdom

500 3 Typewritten Full Name of Fifth Joint Inventor (if any) Colin T Bell  
Given Name Middle Initial Family Name

\*4 Inventor's Signature [Signature]

\*5 Date of Signature 5/7/01  
Month Day Year

\*6 Residence Berkeley Gloucestershire United Kingdom  
City State of Province Country

\*7 Citizenship United Kingdom GBX

8 Post Office Address  
(Insert complete mailing address, including country)  
16 Howmead, Berkeley, Gloucestershire,  
GL13 9AS, United Kingdom

\*Note to Inventors: Please sign name on line 4 exactly as it appears in line 3 and insert the actual date of signing on line 5.  
This form may be executed only when attached to the first page of the Declaration and Power of Attorney form and the specification (including claims) of the application to which it pertains.